



BEHTAM MOLLINTA D 3005



DESCRIPTION

Marine oils especially designed for the crankcase lubrication of slow speed 2 stroke crosshead Diesel engines.

APPLICATIONS

- Crankshaft lubrication
- Oil cooled pistons
- Shaft bearing lubrication

PROPERTIES

- Very good detergency level.
- Very good thermal stability.
- Very good anti-oxidant characteristics.
- Excellent anti-rust and anti-corrosive properties.
- Excellent capacity for water separation.
- Excellent capacity for insoluble separation.
- Good anti-wear properties.
- High resistance to foaming.

CHARACTERISTICS

CHARACTERISTICS	UNITS	BEHTAM MOLLINTA D 3005
S.A.E. Grade		30
Density at 15 °C	kg/m ³	895
Kinematic viscosity at 40 °C	mm ² /s	105
Kinematic viscosity at 100 °C	mm ² /s	11.5
FLASH Point (COC) ASTM D 92	°C	>220
Pour Point	°C	-9
BN (ex TBN) ASTM D 2896	mgKOH/g	5

Characteristics of this chart are indicative typical values

SPECIFICATION

BEHTAM MOLLINTA D 3005 meets the requirements of major Diesel engines builders.

HANDLING, HEALTH AND SAFETY

Lubricants consisting of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.